

PD-24 便携式热敏打印机

作为一款商业级便携式热敏打印机型，可协助工作人员外出现场工作时轻松完成打印作业，打印机内置锂电池，工作时间长，材料使用热敏标签或票据纸，更换耗材方便、打印速度快、品质稳定、印头耐用，主要应用在现场打印的物流标签、客运、铁路、公路、电力等客户群，产品结构创新、部件做工精细、品质稳定可靠，操作极具人性化，深受广大用户的好评！


主要参数

打印精度: 203DPI
 打印宽度: 104MM (纸宽112MM)
 打印方式: 直热方式
 工作级别: 商业级便携式

主要特色

高速处理器，稳定、出色的打印能力
 50MM直径容量纸仓
 标配充电器与锂电池
 齐全的套装
 参数一
 参数二
 参数三

产品性能参数表 PD-24(IrDA) PD-24B(Bluetooth)

打印方式直热方式， Direct Thermal
 打印精度203dpi, 8点/毫米, 832 dots
 打印速度Thermal paper : 400 dot lines /sec (max. 45 dots/line)
 Copy paper : 100 dot lines/sec (max. 45 dots/line) Conditions: room temp. 25 度 / Printing density 0/battery fully charged
 1 ~2英寸/秒 (2.54~50MM/S)
 打印宽度104mm(4.09 in.)
 最大纸宽112MM
 主板内存64 KB
 处 理 器 32位RISC高速处理器
 一维条码Code39,Code128,Code93,CodeBar,UPC-A,UPC-E,JAN(EAN)-13,JAN(EAN)-8
 二维条码PDF417, QR code
 英文字库Roman, Sans Serif, Prestige Elite, Courier Script
 字体点阵12H*24H, 18H*24V (10CPI), 15H*24V (12CPI), 12H*24V (15CPI), 10H*24V (17CPI), 09H*24V (20CPI)
 字符集Characters Codes: ASCII 96 Characters, International Characters(16 Languages + 1 Legal),

<p>IBM Graphics Character, Code Page 33 Page, Window Page 5 page</p> <p>操作面板User Interface 3 keys (Menu, Feed, Power)</p> <p>3 LEDs (Power, Status, Error)</p> <p>Configuration method VuePrint™ menu system</p> <p>指令语言ESC/P, Citizen original commands, ESC/POS (barcode commands only)</p> <p>锂电池参数标配锂电池, Typically 7.2v, 1800 mAh? (Max. voltage DC 8.4V)</p> <p>AC电源参数DC 8.0V (sold separately) When the Battery pack is mounted on the printer, it can be charged using and AC adapter.</p> <p>标配端口IrDA Infrared, RS232C, USB Bluetooth, IrDA Infrared, RS232C, USB</p> <p>标签规格</p> <p>Paper Length Cut sheet</p> <p>paper</p> <p>Min. Paper length: 110mm (4.33 in.)</p> <p>Max. Paper length: 250mm(9.84 in.)</p> <p>纸卷规格</p> <p>Roll paper</p> <p>diameter ,Thermal paper</p> <p>纸卷外径50mm(1.97 in.) ,</p> <p>纸芯内径: 8.0~8.5mm(0.32~0.33 in.)</p> <p>产品规格147 x 140 x 63 mm , 5.79 x 5.51 x 2.48 inches, Values include media roll, mounts and projections</p> <p>产品重量Typical weight 740 g (printer, battery, full paper roll)</p> <p>Printer weight 440 g</p> <p>Battery pack weight 100 g</p> <p>Full paper roll weight 200 g</p> <p>AC charger weight 222 g (excluding power cord)</p> <p>可选配件 RS232 cable</p> <p>USB cable</p> <p>Additional battery</p> <p>Soft carry case, belt clips and straps?</p> <p>External 2-station battery charger?</p> <p>Car adapter / charger</p> <p>使用环境Operating Temperature +5℃ to +40℃ (guaranteed print quality)</p> <p>Operating Humidity 30% to 90% RH, non-condensing</p> <p>Storage Temperature -25℃ to +60℃</p>
<p>客户应用</p> <p>物流配送、现场施式移动打印工作单</p> <p>电力、水费、现场打印, 催缴通知单</p> <p>交警、城管、路政、海关等部门现场违章处罚通知单打印</p> <p>移动现场售票或补票打。</p>